

ScienceDaily®

Two NE tree species can be used in new sustainable building material

Eastern white pine and Eastern hemlock

February 27, 2020

University of Massachusetts Amherst

Two tree species native to the Northeast have been found to be structurally sound for use in cross-laminated timber (CLT) - a revolutionary new type of building material with sought-after sustainability characteristics, according to new research.

Share:

FULL STORY

Two tree species native to the Northeast have been found to be structurally sound for use in cross-laminated timber (CLT) -- a revolutionary new type of building material with sought-after sustainability characteristics, according to research by a University of Massachusetts Amherst timber engineer.

The findings, published in the *Journal of Materials in Civil Engineering*, suggest that these trees -- the eastern hemlock and eastern white pine -- could support local markets for CLT. The manufacturing of CLT, a type of mass timber used for wall, floor and roof construction, could create jobs, improve rural and forestry economies and support better forestry management, which is a strategy to address climate change, the research says.

"This is the future -- prefabricated, panelized wood," says lead author Peggi Clouston, professor of wood mechanics and timber engineering in the School of Earth and Sustainability. "It's far more efficient and there's far less waste than site construction. It's less time- and labor-intensive than building with cast-in-place concrete" and has a much lower carbon footprint.

Clouston's leadership in state-of-the-art wood construction technology was instrumental in the creation of UMass Amherst's John W. Olver Design Building, a showcase for best practices in sustainability. When the structure opened in 2017 to house academic departments and offices, it was considered the most technologically advanced CLT building in the country. All the CLT for the Design Building was FSC-certified, ensuring it came from responsibly managed forests that deliver environmental, social and economic benefits.

"We wanted to show the world how to build a contemporary mass timber structure, and we are doing so. Groups have come from as far away as Taiwan to see it," Clouston says.

Clouston and her team of researchers tested the eastern hemlock and eastern white pine in the UMass Wood Mechanics Lab at the Olver Design Building. They made the composite building panels by gluing together wooden boards from hemlock and pine trees that were grown in the region.



25 April 2020



SENT TO LSU AGCENTER/LOUISIANA FOREST PRODUCTS DEVELOPMENT CENTER - FOREST SECTOR / FORESTY PRODUCTS INTEREST GROUP

"We then broke them in a strength-testing machine to find out if they would be safe to use in a university-size building," Clouston explains.

The researchers analyzed the results, comparing them to engineering requirements, and showed that both tree species met building standards, with eastern hemlock outperforming pine.

Salvaging wood from eastern hemlock is a key forest-management priority, Clouston explains, because the trees are under attack by an insect, the hemlock woolly adelgid. "The insect doesn't harm the wood, but it kills the tree, which in five to 10 years will rot and fall down, becoming hazardous fuel for forest fires," she says.

Eastern hemlock also is considered low-value because it's prone to a wood defect called ring shake and isn't used in structural framing. "Turning this particular species into CLT turns a very low-value material into a very high-value building product," Clouston says.

Identifying low-carbon materials for construction is an emerging buzz among architects, and the timing is right to encourage CLT production in the Northeast, the research concludes.

Story Source:

[Materials](#) provided by [University of Massachusetts Amherst](#). *Note: Content may be edited for style and length.*

Journal Reference:

1. Hamid Kaboli, Peggi L. Clouston, Seth Lawrence. **Feasibility of Two Northeastern Species in Three-Layer ANSI-Approved Cross-Laminated Timber**. *Journal of Materials in Civil Engineering*, 2020; 32 (3): 04020006 DOI: [10.1061/\(ASCE\)MT.1943-5533.0003058](https://doi.org/10.1061/(ASCE)MT.1943-5533.0003058)

Richard P. Vlosky, Ph.D.

Director, Louisiana Forest Products Development Center

Crosby Land & Resources Endowed Professor of Forest Sector Business Development

Room 227, School of Renewable Natural Resources

Louisiana State University, Baton Rouge, LA 70803

Phone (office): (225) 578-4527; Fax: (225) 578-4251; Mobile Phone: (225) 223-1931

Web Site: www.LFPDC.lsu.edu

